



High Voltage Solutions

Transformer T1010P



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	60,000/80,000/100,000
Class	OA/FA/FA
Temp Rise (C)	65
MFG	GE Prolec
Year	2011
Serial	G2687-01
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

NOTES

Brand New Unit, Call for availability, Equipped with a series/parallel connection capable of operating at 138kV as well.

HIGH VOLTAGE

High Voltage (Volts)	69,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	65,550/67,275/69,000/70,725/72,450
HV Range (Volts)	65,550-72,450
HV BIL (kV)	350
CT's HV	Qty (2) C800 MR per phase
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	13,800
LV Range (Volts)	13,800
CT's LV	Qty (2) C800 MR per phase
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	9.588% at 60,000KVA
Core/Coils (lbs)	111,777
Tank/Fittings (lbs)	49,324
Oil Capacity (gals)	9,201
CT's Neutral	None
Flat Beds Req	2
PCB (ppm)	None

SHIPPING

Ship Height (inches)	169
Ship Length (inches)	217
Ship Width (inches)	132
Ship Weight (lbs)	141,499
Assembled	Ships Disassembled