



High Voltage Solutions

Transformer T1017P



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	30,000/40,000/50,000
Class	OA/FA/FA
Temp Rise (C)	65
MFG	GE Prolec
Year	2011
Serial	G2690-01
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

NOTES

Brand New Unit, Call for availability, Equipped with a series/parallel connection capable of operating at 69kV as well.

HIGH VOLTAGE

High Voltage (Volts)	34,500
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	32,775/33,638/34,500/35,363/36,225
HV Range (Volts)	32,775-36,225
HV BIL (kV)	200
CT's HV	Qty (2) C800 MR per phase
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	13,800
LV Range (Volts)	13,800
CT's LV	Qty (2) C800 MR per phase
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	7.798% at 30,000KVA
Core/Coils (lbs)	58,312
Tank/Fittings (lbs)	31,217
Oil Capacity (gals)	4,263
CT's Neutral	None
Flat Beds Req	1
PCB (ppm)	None

SHIPPING

Ship Height (inches)	150
Ship Length (inches)	170
Ship Width (inches)	100
Ship Weight (lbs)	75,519
Assembled	Ships Disassembled