



High Voltage Solutions

Transformer T1017S



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

| | |
|-------------------|----------------------|
| KVA Rating | 30,000/40,000/50,000 |
| Class | OA/FA/FA |
| Temp Rise (C) | 65 |
| MFG | GE Prolec |
| Year | 2011 |
| Serial | G2690-01 |
| Nameplate Drawing | Available |
| Outline Drawing | Available |
| Test Report | Available |

NOTES

Brand New Unit, Call for availability, Equipped with a series/parallel connection capable of operating at 34.5kV as well.

HIGH VOLTAGE

| | |
|----------------------|------------------------------------|
| High Voltage (Volts) | 69,000 |
| HV Vector | Wye |
| Taps High Voltage | DETC |
| HV Taps (Volts) | 65,550/67,275/69,000/70,725/72,450 |
| HV Range (Volts) | 65,550-72,450 |
| HV BIL (kV) | 350 |
| CT's HV | Qty (2) C800 MR per phase |
| HV Bushing | Top |

LOW VOLTAGE

| | |
|---------------------|---------------------------|
| Low Voltage (Volts) | 13,800 |
| LV Vector | Delta |
| Taps Low Voltage | None |
| LV Taps (Volts) | 13,800 |
| LV Range (Volts) | 13,800 |
| CT's LV | Qty (2) C800 MR per phase |
| LV Bushing | Top |

OTHER SPECIFICATIONS

| | |
|---------------------|---------------------|
| Impedance | 7.832% at 30,000KVA |
| Core/Coils (lbs) | 58,312 |
| Tank/Fittings (lbs) | 31,217 |
| Oil Capacity (gals) | 4,263 |
| CT's Neutral | None |
| Flat Beds Req | 1 |
| PCB (ppm) | None |

SHIPPING

| | |
|----------------------|--------------------|
| Ship Height (inches) | 150 |
| Ship Length (inches) | 170 |
| Ship Width (inches) | 100 |
| Ship Weight (lbs) | 75,519 |
| Assembled | Ships Disassembled |