



High Voltage Solutions

# Transformer T1055P



### CONTACT INFO

Phone: 660.829.5100  
 E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)  
 Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	30,000/40,000/50,000
Class	OA/FA/FA
Temp Rise (C)	65
MFG	GE Prolec
Year	2014
Serial	G3113-01
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

### NOTES

Brand New Unit, Call for availability, equipped with a series/parallel connection capable of operating at 138kV as well.

### HIGH VOLTAGE

High Voltage (Volts)	69,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	65,550/67,275/69,000/70,725/72,450
HV Range (Volts)	65,550-72,450
HV BIL (kV)	350
CT's HV	Qty (2) C800 MR per phase
HV Bushing	Top

### LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	13,800
LV Range (Volts)	13,800
CT's LV	Qty (2) C800 MR per phase
LV Bushing	Top

### OTHER SPECIFICATIONS

Impedance	9.337% at 30,000KVA
Core/Coils (lbs)	68,795
Tank/Fittings (lbs)	40,715
Oil Capacity (gals)	7,314
CT's Neutral	Qty (2) C800 MR
Flat Beds Req	2
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	150
Ship Length (inches)	203
Ship Width (inches)	141
Ship Weight (lbs)	94,752
Assembled	Ships Disassembled