



High Voltage Solutions

Transformer T1001



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	7,500/8,400/10,500
Class	OA/OA/FA
Temp Rise (C)	55
MFG	GE
Year	
Serial	L243907B
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	13,800
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	13,200/13,500/13,800/14,100/14,400
HV Range (Volts)	13,200-14,400
HV BIL (kV)	
CT's HV	None
HV Bushing	Side

LOW VOLTAGE

Low Voltage (Volts)	4,160
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	4,160
LV Range (Volts)	4,160
CT's LV	None
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	
Core/Coils (lbs)	
Tank/Fittings (lbs)	
Oil Capacity (gals)	
CT's Neutral	
Flat Beds Req	
PCB (ppm)	

SHIPPING

Ship Height (inches)	138
Ship Length (inches)	112
Ship Width (inches)	102
Ship Weight (lbs)	32,800
Assembled	Ships Assembled