



High Voltage Solutions

## Transformer T1002



### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	1,500
Class	OA
Temp Rise (C)	65
MFG	GE
Year	
Serial	H-883464A
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

### NOTES

Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	13,800
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	13,200/13,500/13,800/14,100/14,400
HV Range (Volts)	13,200-14,400
HV BIL (kV)	
CT's HV	None
HV Bushing	Side

### LOW VOLTAGE

Low Voltage (Volts)	4,160
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	4,160
LV Range (Volts)	4,160
CT's LV	None
LV Bushing	Side

### OTHER SPECIFICATIONS

Impedance	5.43% at 13,800-4,160V and 1,500KVA
Core/Coils (lbs)	3,500
Tank/Fittings (lbs)	2,650
Oil Capacity (gals)	232
CT's Neutral	None
Flat Beds Req	None
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	101
Ship Length (inches)	116
Ship Width (inches)	62
Ship Weight (lbs)	7,875
Assembled	Ships Assembled