



High Voltage Solutions

Transformer T1004



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	500
Class	OA
Temp Rise (C)	55
MFG	Westinghouse
Year	1986
Serial	PAT2658-0101
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	12,470
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	11,850/12,160/12,470/12,780/13,090
HV Range (Volts)	11,850-13,090
HV BIL (kV)	95
CT's HV	None
HV Bushing	Side

LOW VOLTAGE

Low Voltage (Volts)	480
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	480
LV Range (Volts)	480
CT's LV	None
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	5.2% at 12,470-480V and 500KVA
Core/Coils (lbs)	5,365
Tank/Fittings (lbs)	1,262
Oil Capacity (gals)	121
CT's Neutral	None
Flat Beds Req	None
PCB (ppm)	None

SHIPPING

Ship Height (inches)	90
Ship Length (inches)	81
Ship Width (inches)	64
Ship Weight (lbs)	7,527
Assembled	Ships Assembled