



High Voltage Solutions

## Transformer T1005



### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	500
Class	OA
Temp Rise (C)	55
MFG	Westinghouse
Year	1986
Serial	PAT2658-0102
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

### NOTES

Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	12,470
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	11,850/12,150/12,470/12,780/13,090
HV Range (Volts)	11,850-13,090
HV BIL (kV)	95
CT's HV	None
HV Bushing	Side

### LOW VOLTAGE

Low Voltage (Volts)	480
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	480
LV Range (Volts)	480
CT's LV	None
LV Bushing	Side

### OTHER SPECIFICATIONS

Impedance	5.2% at 12,470-480V and 500KVA
Core/Coils (lbs)	5,365
Tank/Fittings (lbs)	1,262
Oil Capacity (gals)	121
CT's Neutral	None
Flat Beds Req	None
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	90
Ship Length (inches)	81
Ship Width (inches)	64
Ship Weight (lbs)	7,527
Assembled	Ships Assembled