



High Voltage Solutions

## Transformer T1021



### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	132,000/176,000/220,000
Class	OA/FA/FA
Temp Rise (C)	65
MFG	GE Prolec
Year	2014
Serial	G3273-02
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

### NOTES

Brand New Unit, Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	138,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	131,100/134,550/138,000/141,450/144,900
HV Range (Volts)	131,100-144,900
HV BIL (kV)	550
CT's HV	Qty (2) 1,200:5; C800 MR per phase
HV Bushing	Top

### LOW VOLTAGE

Low Voltage (Volts)	18,000
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	18,000
LV Range (Volts)	18,000
CT's LV	Qty (2) 8,000:5; C800 MR per phase
LV Bushing	Top

### OTHER SPECIFICATIONS

Impedance	8.7% at 138,000-18,000V and 132,000KVA
Core/Coils (lbs)	201,170
Tank/Fittings (lbs)	73,440
Oil Capacity (gals)	11,279
CT's Neutral	Qty (1) 1,200:5 C800 MR on HO
Flat Beds Req	3
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	187
Ship Length (inches)	245
Ship Width (inches)	136
Ship Weight (lbs)	245,095
Assembled	Ships Disassembled via Rail