



High Voltage Solutions

Transformer T1018

No Image Available

CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	1,500
Class	OA
Temp Rise (C)	65
MFG	GE
Year	
Serial	H-883847
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	13,800
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	13,200/13,500/13,800/14,100/14,400
HV Range (Volts)	13,200-14,400
HV BIL (kV)	
CT's HV	None
HV Bushing	Side

LOW VOLTAGE

Low Voltage (Volts)	4,160
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	4,160
LV Range (Volts)	4,160
CT's LV	None
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	5.48% at 13,800-4,160V and 1,500KVA
Core/Coils (lbs)	3,450
Tank/Fittings (lbs)	2,300
Oil Capacity (gals)	190
CT's Neutral	None
Flat Beds Req	None
PCB (ppm)	None

SHIPPING

Ship Height (inches)	82
Ship Length (inches)	105
Ship Width (inches)	80
Ship Weight (lbs)	7,170
Assembled	Ships Assembled