



High Voltage Solutions

Transformer T1030



CONTACT INFO

Phone: 660.829.5100
 E-mail: hvsales@proenergyservices.com
 Website: proenergyservices.com

GENERAL SPECIFICATIONS

| | |
|-------------------|-------------------------|
| KVA Rating | 132,000/176,000/220,000 |
| Class | OA/FA/FA |
| Temp Rise (C) | 65 |
| MFG | GE Prolec |
| Year | 2014 |
| Serial | G3273-01 |
| Nameplate Drawing | Available |
| Outline Drawing | Available |
| Test Report | Available |

NOTES

Brand New Unit, Call for availability.

HIGH VOLTAGE

| | |
|----------------------|-----------------------------------------|
| High Voltage (Volts) | 138,000 |
| HV Vector | Wye |
| Taps High Voltage | DETC |
| HV Taps (Volts) | 131,100/134,550/138,000/141,450/144,900 |
| HV Range (Volts) | 131,100-144,900 |
| HV BIL (kV) | 650 |
| CT's HV | Qty (2) 1,200:5; C800 MR per phase |
| HV Bushing | Top |

LOW VOLTAGE

| | |
|---------------------|------------------------------------|
| Low Voltage (Volts) | 18,000 |
| LV Vector | Delta |
| Taps Low Voltage | None |
| LV Taps (Volts) | 18,000 |
| LV Range (Volts) | 18,000 |
| CT's LV | Qty (2) 8,000:5; C800 MR per phase |
| LV Bushing | Top |

OTHER SPECIFICATIONS

| | |
|---------------------|------------------------------------------|
| Impedance | 8.727% at 115,000-18,000V and 132,000KVA |
| Core/Coils (lbs) | 201,170 |
| Tank/Fittings (lbs) | 73,440 |
| Oil Capacity (gals) | 11,279 |
| CT's Neutral | Qty (1) 1,200:5 C800 MR on HO |
| Flat Beds Req | 3 |
| PCB (ppm) | None |

SHIPPING

| | |
|----------------------|-----------------------------|
| Ship Height (inches) | 187 |
| Ship Length (inches) | 245 |
| Ship Width (inches) | 136 |
| Ship Weight (lbs) | 245,095 |
| Assembled | Ships Disassembled via Rail |