



High Voltage Solutions

Transformer T1026

No Image Available

CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	1,500
Class	OA
Temp Rise (C)	55
MFG	Fortune
Year	2003
Serial	D0224 09
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	4,160
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	3,952/4,056/4,160/4,264/4,368
HV Range (Volts)	3,952-4,368
HV BIL (kV)	75
CT's HV	None
HV Bushing	Side

LOW VOLTAGE

Low Voltage (Volts)	480
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	480
LV Range (Volts)	480
CT's LV	None
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	6% at 4,160-480V and 1,500KVA
Core/Coils (lbs)	
Tank/Fittings (lbs)	
Oil Capacity (gals)	408
CT's Neutral	None
Flat Beds Req	NA
PCB (ppm)	None

SHIPPING

Ship Height (inches)	75
Ship Length (inches)	102
Ship Width (inches)	96
Ship Weight (lbs)	5,815
Assembled	Ships Assembled