



High Voltage Solutions

## Transformer T1033-9.2



### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	100,000
Class	FOA
Temp Rise (C)	65
MFG	ABB
Year	1996
Serial	93902
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

### NOTES

Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	230,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	218,500/224,250/230,000/235,750/241,500
HV Range (Volts)	218,500-241,500
HV BIL (kV)	900
CT's HV	Qty (1) C800 MR per phase
HV Bushing	Top

### LOW VOLTAGE

Low Voltage (Volts)	9,200
LV Vector	Delta
Taps Low Voltage	LTC
LV Taps (Volts)	6,200/6,388/6,575/6,763/6,950/7,138/7,325 7,513/7,700/7,888/8,075/8,263/8,450/8,638 8,825/9,013/9,200/9,388/9,575/9,763/9,950 10,138/10,325/10,513/10,700/10,888/11,075 11,263/11,450/11,638/11,825/12,013/12,200
LV Range (Volts)	6,200-12,200
CT's LV	Qty (1) C800 SR per phase
LV Bushing	Top

### OTHER SPECIFICATIONS

Impedance	15% at 100,000KVA & 230kV-16.05kV
Core/Coils (lbs)	153,000
Tank/Fittings (lbs)	83,000
Oil Capacity (gals)	15,700
CT's Neutral	Qty (1) C800 MR
Flat Beds Req	2
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	192
Ship Length (inches)	342
Ship Width (inches)	152
Ship Weight (lbs)	211,640
Assembled	Ships Disassembled