



High Voltage Solutions

Transformer T1034

No Image Available

CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	1,500/1,680
Class	OA
Temp Rise (C)	65
MFG	Cooper
Year	
Serial	0026002086
Nameplate Drawing	Not Available
Outline Drawing	Not Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	13,800
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	13,110/13,460/13,800/14,150/14,490
HV Range (Volts)	13,110-14,490
HV BIL (kV)	95
CT's HV	None
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	2,400
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	2,400
LV Range (Volts)	2,400
CT's LV	None
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	5.2% at 13,800-2,400V and 1,500KVA
Core/Coils (lbs)	4,490
Tank/Fittings (lbs)	3,250
Oil Capacity (gals)	484
CT's Neutral	None
Flat Beds Req	NA
PCB (ppm)	None

SHIPPING

Ship Height (inches)	
Ship Length (inches)	
Ship Width (inches)	
Ship Weight (lbs)	11,350
Assembled	Ships Assembled