



High Voltage Solutions

## Transformer T1037

No Image Available

### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	2,000
Class	OA
Temp Rise (C)	55
MFG	Schaffner
Year	1999
Serial	49467
Nameplate Drawing	Not Available
Outline Drawing	Not Available
Test Report	Not Available

### NOTES

50Hz Unit, Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	11,500
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	10,925/11,212/11,500/11,788/12,075
HV Range (Volts)	10,925-12,075
HV BIL (kV)	110
CT's HV	None
HV Bushing	Side

### LOW VOLTAGE

Low Voltage (Volts)	3,300
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	3,300
LV Range (Volts)	3,300
CT's LV	None
LV Bushing	Side

### OTHER SPECIFICATIONS

Impedance	5.42% at 2,000KVA
Core/Coils (lbs)	
Tank/Fittings (lbs)	
Oil Capacity (gals)	400
CT's Neutral	None
Flat Beds Req	NA
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	
Ship Length (inches)	
Ship Width (inches)	
Ship Weight (lbs)	13,000
Assembled	Ships Assembled