



High Voltage Solutions

Transformer T1038

No Image Available

CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	2,000
Class	OA
Temp Rise (C)	55
MFG	Schaffner
Year	1999
Serial	49468
Nameplate Drawing	Not Available
Outline Drawing	Not Available
Test Report	Not Available

NOTES

50Hz Unit, Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	11,500
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	10,925/11,212/11,500/11,788/12,075
HV Range (Volts)	10,925-12,075
HV BIL (kV)	110
CT's HV	None
HV Bushing	Side

LOW VOLTAGE

Low Voltage (Volts)	3,300
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	3,300
LV Range (Volts)	3,300
CT's LV	None
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	5.42% at 2,000KVA
Core/Coils (lbs)	
Tank/Fittings (lbs)	
Oil Capacity (gals)	400
CT's Neutral	None
Flat Beds Req	NA
PCB (ppm)	None

SHIPPING

Ship Height (inches)	
Ship Length (inches)	
Ship Width (inches)	
Ship Weight (lbs)	13,000
Assembled	Ships Assembled