



High Voltage Solutions

Transformer T1042

No Image Available

CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	7,500/10,500
Class	ONAN/ONAF
Temp Rise (C)	65
MFG	TR
Year	2011
Serial	100511-13
Nameplate Drawing	Not Available
Outline Drawing	Available
Test Report	Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	18,920
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	17,930/18,430/18,920/19,420/19,920
HV Range (Volts)	17,930-19,920
HV BIL (kV)	150
CT's HV	None
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	4,160
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	4,160
LV Range (Volts)	4,160
CT's LV	None
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	8.1% at 7,500KVA
Core/Coils (lbs)	
Tank/Fittings (lbs)	
Oil Capacity (gals)	2,850
CT's Neutral	None
Flat Beds Req	N/A
PCB (ppm)	None

SHIPPING

Ship Height (inches)	172
Ship Length (inches)	152
Ship Width (inches)	115
Ship Weight (lbs)	67,900
Assembled	Ships Assembled