



High Voltage Solutions

## Transformer T1053

No Image Available

### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	78,000/104,000/130,000/146,000
Class	OA/FA/FA
Temp Rise (C)	65
MFG	Ferranti Packard
Year	1996
Serial	TP-273
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

### NOTES

Refurbished, Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	230,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	218,500/224,250/230,000/235,750/241,500
HV Range (Volts)	218,500-241,500
HV BIL (kV)	900
CT's HV	Qty (3) C800 MR per phase
HV Bushing	Top

### LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	13,800
LV Range (Volts)	13,800
CT's LV	Qty (1) C800 MR per phase
LV Bushing	Top

### OTHER SPECIFICATIONS

Impedance	9.5% at 78,000KVA
Core/Coils (lbs)	134,123
Tank/Fittings (lbs)	62,438
Oil Capacity (gals)	11,374
CT's Neutral	Qty (1) C800 MR per phase
Flat Beds Req	2
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	189
Ship Length (inches)	320
Ship Width (inches)	139
Ship Weight (lbs)	165,383
Assembled	Ships Disassembled