



High Voltage Solutions

## Transformer T1062



### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	2,500/2,900
Class	OA
Temp Rise (C)	65
MFG	Cooper-McGraw
Year	1987
Serial	C-46338-1-1
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

### NOTES

Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	13,800
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	13,200/13,500/13,800/14,100/14,400
HV Range (Volts)	13,200-14,400
HV BIL (kV)	110
CT's HV	Qty (1) 2,000:5 SR and (1) 200:5 SR per phase
HV Bushing	Side

### LOW VOLTAGE

Low Voltage (Volts)	4,160
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	4,160
LV Range (Volts)	4,160
CT's LV	None
LV Bushing	Side

### OTHER SPECIFICATIONS

Impedance	5.6% at 13,800-480V and 2,500KVA
Core/Coils (lbs)	8,950
Tank/Fittings (lbs)	3,600
Oil Capacity (gals)	530
CT's Neutral	(1) 200:5 SR
Flat Beds Req	None
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	
Ship Length (inches)	
Ship Width (inches)	
Ship Weight (lbs)	16,525
Assembled	Ships Assembled