



High Voltage Solutions

Transformer T1063



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	21,000/28,000/35,000
Class	OA/FA/FA
Temp Rise (C)	55
MFG	ASEA
Year	
Serial	A0342T
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	23,000
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	21,850/22,425/23,000/23,575/24,150
HV Range (Volts)	21,850-24,150
HV BIL (kV)	150
CT's HV	Qty (2) C400 MR per phase
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	13,800
LV Range (Volts)	13,800
CT's LV	Qty (1) C400 MR per phase
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	5.98% at 23,000-13,800 and 21,000KVA
Core/Coils (lbs)	50,000
Tank/Fittings (lbs)	25,500
Oil Capacity (gals)	2,940
CT's Neutral	None
Flat Beds Req	None
PCB (ppm)	None

SHIPPING

Ship Height (inches)	
Ship Length (inches)	
Ship Width (inches)	
Ship Weight (lbs)	97,600
Assembled	Ships Assembled