



High Voltage Solutions

Transformer T1058S



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	30,000/40,000/57,000
Class	OA/FA/FA
Temp Rise (C)	65
MFG	GE Prolec
Year	2014
Serial	G3114-02
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

NOTES

Brand New Unit, Call for availability, Equipped with a series/parallel connection capable of operating at 34.5kV as well.

HIGH VOLTAGE

High Voltage (Volts)	69,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	65,550/67,275/69,000/70,725/72,450
HV Range (Volts)	65,550-72,450
HV BIL (kV)	350
CT's HV	Qty (2) C800 MR per phase
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	13,800
LV Range (Volts)	13,800
CT's LV	Qty (2) C800 MR per phase
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	7.779% at 30,000KVA
Core/Coils (lbs)	58,312
Tank/Fittings (lbs)	35,685
Oil Capacity (gals)	4,428
CT's Neutral	Qty (2) C800 MR
Flat Beds Req	1
PCB (ppm)	None

SHIPPING

Ship Height (inches)	150
Ship Length (inches)	170
Ship Width (inches)	100
Ship Weight (lbs)	75,627
Assembled	Ships Disassembled