



High Voltage Solutions

Transformer T1074



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

| | |
|-------------------|----------------------|
| KVA Rating | 15,000/20,000/25,000 |
| Class | OA/FA/FA |
| Temp Rise (C) | 65 |
| MFG | GE Prolec |
| Year | 1996 |
| Serial | R280060A |
| Nameplate Drawing | Available |
| Outline Drawing | Available |
| Test Report | Available |

NOTES

Call for availability.

HIGH VOLTAGE

| | |
|----------------------|---|
| High Voltage (Volts) | 38,000 |
| HV Vector | Wye |
| Taps High Voltage | LTC |
| HV Taps (Volts) | 34,200/34,438/34,675/34,913/35,150/35,388 35,625/35,863/36,100/36,338/36,575/36,813 37,050/37,288/37,525/37,763/38,000/38,238 38,475/38,713/38,950/39,188/39,425/39,663 39,900/40,138/40,375/40,613/40,850/41,088 41,325/41,563/41,800 |
| HV Range (Volts) | 34,200-41,800 |
| HV BIL (kV) | 200 |
| CT's HV | Qty (1) C200 MR on H2 & H3 |
| HV Bushing | Top |

LOW VOLTAGE

| | |
|---------------------|----------------------|
| Low Voltage (Volts) | 13,800 |
| LV Vector | Delta |
| Taps Low Voltage | None |
| LV Taps (Volts) | 13,800 |
| LV Range (Volts) | 13,800 |
| CT's LV | Qty (1) C50 MR on X2 |
| LV Bushing | Top |

OTHER SPECIFICATIONS

| | |
|---------------------|---------------------|
| Impedance | 5.705% at 15,000KVA |
| Core/Coils (lbs) | 47,455 |
| Tank/Fittings (lbs) | 20,994 |
| Oil Capacity (gals) | 4,304 |
| CT's Neutral | Qty (1) C200 MR |
| Flat Beds Req | 1 |
| PCB (ppm) | None |

SHIPPING

| | |
|----------------------|--------------------|
| Ship Height (inches) | 152 |
| Ship Length (inches) | 191 |
| Ship Width (inches) | 91 |
| Ship Weight (lbs) | 61,813 |
| Assembled | Ships Disassembled |