



## High Voltage Solutions

# Transformer T1074-50



### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	12,500/16,667/20,833
Class	OA/FA/FA
Temp Rise (C)	65
MFG	GE Prolec
Year	1996
Serial	R280060A
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

### NOTES

50Hz Unit, Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	31,667
HV Vector	Wye
Taps High Voltage	LTC
HV Taps (Volts)	28,500/28,698/28,896/29,094/29,292/29,490 29,688/29,886/30,083/30,282/30,479/30,678 30,875/31,073/31,271/31,469/31,667/31,865 32,063/32,261/32,458/32,657/32,854/33,053 33,250/33,448/33,646/33,844/34,042/34,240 34,438/34,636/34,833
HV Range (Volts)	28,500-34,833
HV BIL (kV)	200
CT's HV	Qty (1) C200 MR on H2 & H3
HV Bushing	Top

### LOW VOLTAGE

Low Voltage (Volts)	11,500
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	11,500
LV Range (Volts)	11,500
CT's LV	Qty (1) C50 MR on X2
LV Bushing	Top

### OTHER SPECIFICATIONS

Impedance	4.754% at 12,500KVA
Core/Coils (lbs)	47,455
Tank/Fittings (lbs)	20,994
Oil Capacity (gals)	4,304
CT's Neutral	Qty (1) C200 MR
Flat Beds Req	1
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	152
Ship Length (inches)	191
Ship Width (inches)	91
Ship Weight (lbs)	61,813
Assembled	Ships Disassembled