



High Voltage Solutions

Transformer T1022



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	132,000/176,000/220,000
Class	OA/FA/FA
Temp Rise (C)	65
MFG	GE Prolec
Year	2010
Serial	G2547-03
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

NOTES

Brand New Unit, Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	115,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	109,250/112,125/115,000/117,875/120,750
HV Range (Volts)	109,250/120,750
HV BIL (kV)	550
CT's HV	Qty (2) 1,200:5 C800 MR per phase
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	18,000
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	18,000
LV Range (Volts)	18,000
CT's LV	Qty (2) 8,000:5 C800 MR per phase
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	8.902% at 115,000-18,000V and 132,000KVA
Core/Coils (lbs)	201,170
Tank/Fittings (lbs)	73,440
Oil Capacity (gals)	11,279
CT's Neutral	Qty (1) 1,200:5 C800 MR per H0
Flat Beds Req	3
PCB (ppm)	None

SHIPPING

Ship Height (inches)	187
Ship Length (inches)	245
Ship Width (inches)	136
Ship Weight (lbs)	245,095
Assembled	Ships Disassembled via Rail