



High Voltage Solutions

Transformer T1072



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	25,000
Class	ONAF
Temp Rise (C)	65
MFG	National Industri
Year	1989
Serial	10160
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	69,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	59,800/60,900/62,100/63,200/64,400/65,500 66,700/67,800/69,000/70,200/71,300/72,500 73,600/74,800/75,900/77,100/78,200
HV Range (Volts)	59,800-78,200
HV BIL (kV)	325
CT's HV	None
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	13,800
LV Range (Volts)	13,800
CT's LV	None
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	11.11% at 25MVA
Core/Coils (lbs)	38,600
Tank/Fittings (lbs)	17,000
Oil Capacity (gals)	2,600
CT's Neutral	None
Flat Beds Req	2
PCB (ppm)	None

SHIPPING

Ship Height (inches)	111
Ship Length (inches)	162
Ship Width (inches)	64
Ship Weight (lbs)	55,600
Assembled	Ships Disassembled