



High Voltage Solutions

Transformer T1072-50



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	20,800
Class	ONAF
Temp Rise (C)	65
MFG	National Industri
Year	1989
Serial	10160
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Not Available

NOTES

50Hz Unit, Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	57,500
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	49,833/50,750/51,750/52,667/53,667/54,583 55,583/56,500/57,500/58,500/59,417/60,417 61,333/62,333/63,250/64,250/65,167
HV Range (Volts)	49,833-65,157
HV BIL (kV)	325
CT's HV	None
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	11,500
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	11,500
LV Range (Volts)	11,500
CT's LV	None
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	9.26% at 20.8MVA
Core/Coils (lbs)	38,600
Tank/Fittings (lbs)	17,000
Oil Capacity (gals)	2,600
CT's Neutral	None
Flat Beds Req	2
PCB (ppm)	None

SHIPPING

Ship Height (inches)	111
Ship Length (inches)	162
Ship Width (inches)	64
Ship Weight (lbs)	55,600
Assembled	Ships Disassembled