



High Voltage Solutions

## Transformer T1073-50



### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	20,800
Class	ONAF
Temp Rise (C)	65
MFG	National Industri
Year	1989
Serial	10161
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Not Available

### NOTES

50Hz Unit, Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	57,500
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	49,833/50,750/51,750/52,667/53,667/54,583 55,583/56,500/57,500/58,500/59,417/60,417 61,333/62,333/63,250/64,250/65,167
HV Range (Volts)	49,833-65,157
HV BIL (kV)	325
CT's HV	None
HV Bushing	Top

### LOW VOLTAGE

Low Voltage (Volts)	11,500
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	11,500
LV Range (Volts)	11,500
CT's LV	None
LV Bushing	Top

### OTHER SPECIFICATIONS

Impedance	8.89% at 20.8MVA
Core/Coils (lbs)	38,600
Tank/Fittings (lbs)	17,000
Oil Capacity (gals)	2,600
CT's Neutral	None
Flat Beds Req	2
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	111
Ship Length (inches)	162
Ship Width (inches)	64
Ship Weight (lbs)	55,600
Assembled	Ships Disassembled