



High Voltage Solutions

Transformer T1075



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	39,200/52,200/65,300
Class	OA/FA/FA
Temp Rise (C)	65
MFG	Magnetek
Year	1990
Serial	A0947T
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	115,000
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	109,250/112,125/115,000/117,875/120,750
HV Range (Volts)	109,250-120,750
HV BIL (kV)	450
CT's HV	Qty (2) C400 MR per phase
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Wye
Taps Low Voltage	OLTC
LV Taps (Volts)	12,420/12,510/12,590/12,680/12,770/12,850 12,940/13,020/13,110/13,200/13,280/13,370 13,450/13,540/13,630/13,710/13,800/13,890 13,970/14,060/14,140/14,230/14,320/14,400 14,490/14,580/14,660/14,750/14,830/14,920 15,010/15,090/15,180
LV Range (Volts)	12,420-15,180
CT's LV	None
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	9.73% at 35MVA
Core/Coils (lbs)	72,600
Tank/Fittings (lbs)	56,800
Oil Capacity (gals)	6,680
CT's Neutral	None
Flat Beds Req	1
PCB (ppm)	None

SHIPPING

Ship Height (inches)	176
Ship Length (inches)	178
Ship Width (inches)	123
Ship Weight (lbs)	100,800
Assembled	Ships Disassembled