




High Voltage Solutions

Transformer T1094



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	12,500/14,000/16,667/18,667
Class	ONAN/ONAF
Temp Rise (C)	65
MFG	Virginia Transformer
Year	2010
Serial	44013MA001-B359B
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

NOTES

New Unit, Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	13,200
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	12,540/12,870/13,200/13,530/13,860
HV Range (Volts)	12,540-13,860
HV BIL (kV)	150
CT's HV	None
HV Bushing	Side

LOW VOLTAGE

Low Voltage (Volts)	4,160
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	4,160
LV Range (Volts)	4,160
CT's LV	Qty (1) C800 MR per phase
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	6.58% at 12,500KVA
Core/Coils (lbs)	29,400
Tank/Fittings (lbs)	26,140
Oil Capacity (gals)	2,246
CT's Neutral	Qty (1) C800 MR
Flat Beds Req	1
PCB (ppm)	None

SHIPPING

Ship Height (inches)	142
Ship Length (inches)	182
Ship Width (inches)	141
Ship Weight (lbs)	73,250
Assembled	Ships Fully Assembled less (1) Radiator w/Fans