



High Voltage Solutions

Transformer T1089P



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	45,000/60,000/75,000
Class	OA/FA/FA
Temp Rise (C)	65
MFG	GE Prolec
Year	2015
Serial	G3112-02
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

NOTES

New Unit, Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	69,000
HV Vector	Wye
Taps High Voltage	DETC
HV Taps (Volts)	65,550/67,280/69,000/70,730/72,450
HV Range (Volts)	65,550-72,450
HV BIL (kV)	650
CT's HV	Qty (2) C800 MR per phase
HV Bushing	Top

LOW VOLTAGE

Low Voltage (Volts)	13,800
LV Vector	Delta
Taps Low Voltage	None
LV Taps (Volts)	13,800
LV Range (Volts)	13,800
CT's LV	Qty (2) C800 MR per phase
LV Bushing	Top

OTHER SPECIFICATIONS

Impedance	9.477% at 45,000KVA
Core/Coils (lbs)	84,289
Tank/Fittings (lbs)	48,447
Oil Capacity (gals)	8,937
CT's Neutral	Qty (2) C800 MR
Flat Beds Req	2
PCB (ppm)	None

SHIPPING

Ship Height (inches)	168
Ship Length (inches)	208
Ship Width (inches)	130
Ship Weight (lbs)	111,307
Assembled	Ships Disassembled via Truck with Oil