



High Voltage Solutions

Transformer T1084



CONTACT INFO

Phone: 660.829.5100
 E-mail: hvsales@proenergyservices.com
 Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	1,000/1,288
Class	OA/FA
Temp Rise (C)	65
MFG	Westinghouse
Year	1984
Serial	PAW1118-0102
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	4,160
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	3,950/4,055/4,160/4,260/4,360
HV Range (Volts)	3,950-4,360
HV BIL (kV)	
CT's HV	None
HV Bushing	Side

LOW VOLTAGE

Low Voltage (Volts)	480
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	480
LV Range (Volts)	480
CT's LV	None
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	5.54% @ 4,160-480V and 1,000 KVA
Core/Coils (lbs)	2,783
Tank/Fittings (lbs)	2,506
Oil Capacity (gals)	206
CT's Neutral	Qty (1) 1,200:5 MR on X0
Flat Beds Req	None
PCB (ppm)	None

SHIPPING

Ship Height (inches)	
Ship Length (inches)	
Ship Width (inches)	
Ship Weight (lbs)	8,111
Assembled	Ships Assembled