



High Voltage Solutions

Transformer T1085



CONTACT INFO

Phone: 660.829.5100

E-mail: hvsales@proenergyservices.com

Website: proenergyservices.com

GENERAL SPECIFICATIONS

KVA Rating	2,500/3,200
Class	OA/FA
Temp Rise (C)	65
MFG	Westinghouse
Year	1984
Serial	PAW1119-0101
Nameplate Drawing	Available
Outline Drawing	Not Available
Test Report	Not Available

NOTES

Call for availability.

HIGH VOLTAGE

High Voltage (Volts)	4,160
HV Vector	Delta
Taps High Voltage	DETC
HV Taps (Volts)	3,950/4,055/4,160/4,260/4,360
HV Range (Volts)	3,950-4,360
HV BIL (kV)	
CT's HV	None
HV Bushing	Side

LOW VOLTAGE

Low Voltage (Volts)	480
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	480
LV Range (Volts)	480
CT's LV	None
LV Bushing	Side

OTHER SPECIFICATIONS

Impedance	5.24% @ 4,160-480V and 2,500 KVA
Core/Coils (lbs)	5,997
Tank/Fittings (lbs)	3,283
Oil Capacity (gals)	318
CT's Neutral	Qty (1) 3,000:5 MR on X0
Flat Beds Req	None
PCB (ppm)	None

SHIPPING

Ship Height (inches)	
Ship Length (inches)	
Ship Width (inches)	
Ship Weight (lbs)	13,578
Assembled	Ships Assembled