



## High Voltage Solutions

# Transformer T1107

No Image Available

### CONTACT INFO

Phone: 660.829.5100

E-mail: [hvsales@proenergyservices.com](mailto:hvsales@proenergyservices.com)

Website: [proenergyservices.com](http://proenergyservices.com)

### GENERAL SPECIFICATIONS

KVA Rating	94,800/126,400/158,000
Class	ONAN/ONAF/ONAF
Temp Rise (C)	65
MFG	GE Prolec
Year	2016
Serial	G3483-01
Nameplate Drawing	Available
Outline Drawing	Available
Test Report	Available

### NOTES

Brand New Unit, Call for availability.

### HIGH VOLTAGE

High Voltage (Volts)	138,000
HV Vector	Wye
Taps High Voltage	OLTC
HV Taps (Volts)	124,200/125,075/125,925/126,800/127,650 128,525/129,375/130,250/131,100/131,975 132,825/133,700/134,550/135,425/136,275 137,150/138,000/138,675/139,725/140,600 141,450/142,325/143,175/144,050/144,900 145,775/146,625/147,500/148,350/149,225 150,075/150,950/151,800
HV Range (Volts)	124,200-151,800
HV BIL (kV)	550
CT's HV	Qty (1) 0.15B1.8 per Phase
HV Bushing	Top

### LOW VOLTAGE

Low Voltage (Volts)	34,500
LV Vector	Wye
Taps Low Voltage	None
LV Taps (Volts)	34,500
LV Range (Volts)	34,500
CT's LV	Qty (3) C400 MR per Phase & Qty (1) 0.15B1.8 SR per Phase
LV Bushing	Top

### OTHER SPECIFICATIONS

Impedance	8.295% @ 94,800 KVA
Core/Coils (lbs)	172,810
Tank/Fittings (lbs)	79,975
Oil Capacity (gals)	13,278
CT's Neutral	Qty (1) C400 MR on H0 & X0
Flat Beds Req	2
PCB (ppm)	None

### SHIPPING

Ship Height (inches)	172
Ship Length (inches)	324
Ship Width (inches)	134
Ship Weight (lbs)	219,200
Assembled	Ships Disassembled